

STADT WOLF

46 t bp Voith-Schneider

Tractor tug



Built:	1993	Gross Tonnage:	287 ts
Length:	31,57 m	Classification:	GL + 100 A5 E TUG
Breadth:	10,22 m	Bunker Capacity:	136 ts
Draft:	5,35 m	Bollard Pull:	46 ts
Airdraft:	16,90 m	Speed:	12 knots

Propulsion: Twin-Voith-Propeller 28 G II / 185

Main Engines: 2 MAK Type 8 M 332 C, total 4.315 bhp

Bridge: GMDSS A2, Inmarsat M, 2 VHF, Mobile phone GSM, Echosounder, Gyro Satnav DGPS, 2 Radars, Autopilot, Electronic Chart, Radio Direction Finder, 2 Searchlights each 1000 W.

Accommodation: 4 single cabins with 1 reserve berth each and 2 twin cabins. All quarters are air conditioned

Towing gear: 1 waterfall doubledrum hydraulic towing winch with 20 tons pull 83 tons brake holding load
One drum carries a wire of 150 m length / 40 mm dia.
One drum carries a wire of 700 m length / 40 mm dia.
One spare wire of 700 m length / 40 mm dia.
Extensive supply of spare wires, perlon hawsers, chain and wire bridles etc.

Pumps: Ample supply of portable Diesel and electric submersible pumps

Mooring Equipment: 1 combined anchor/mooring winch with 1 mooring drum on the foredeck.
Anchor handling: 1 stern slide for anchor handling purposes (Anchor cannot be taken on deck)

Anchor handling: 1 stern slide for anchor handling purposes (Anchor cannot be taken on deck)

Crane: 1 on the aft deck:0,95 tons S.W.L. max. 3 m outreach.

Particulars of this unit and inventory believed correct at time of printing but subject to change. Printed August 2009 replacing all previously printed particulars

Stadt Sjøtransport AS

P.O. Box 33, N-6721 Svelgen, Norway
Tel: +47 5779 3100 / +47 9188 4528 - Fax: +47 5779 3104
Email: post@tugs.no
www.tugs.no

